

Dekafix DEK 5/6.5 MC NE WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| | |
|--------------------|----------------------------------------------------------------------------------|
| Type | DEK 5/6.5 MC NE WS |
| Order No. | 1609840000 |
| Version | Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50 Weidmueller, white |
| GTIN (EAN) | 4008190203429 |
| Qty. | 900 pc(s). |
| compatible printer | 1324380000 2438520000 2438510000 |

Data sheet

Dekafix DEK 5/6.5 MC NE WS

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|--------|-----------------|------------|
| Width | 6.5 mm | Width (inches) | 0.256 inch |
| Height | 5 mm | Height (inches) | 0.197 inch |
| Net weight | 0.14 g | | |

General data

| | | | |
|----------------------------------------------|-------------|-----------------------------|--------------|
| Application/manufacture | Weidmueller | Colour | white |
| Halogen | No | Material | Polyamide 66 |
| Material colour according to resistance code | 9 | Operating temperature range | -40...100 °C |
| UL 94 flammability rating | V-2 | Width | 6.5 mm |

Connector markers

| | |
|-----------------|--------|
| Pitch in mm (P) | 6.5 mm |
|-----------------|--------|

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000761 | ETIM 7.0 | EC000761 |
| eClass 9.0 | 27-14-11-37 | eClass 9.1 | 27-14-11-37 |
| eClass 10.0 | 27-14-11-37 | UNSPSC | 30-21-18-07 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Brochure/Catalogue | CAT 1 TERM 16/17 EN |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | STEP |
| Product Change Notification | Technical change to MultiCard material - DE Technical change to MultiCard material - EN |
| Software | M-Print PRO configuration file |

Data sheet

Dekafix
DEK 5/6.5 MC NE WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings



Drawing

