


## SlimFix Clip SFC 2.5/21 MC NE GE

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Similar to illustration

The SlimFix Clip combines two advantages: its unique closure mechanism offers the reliability of a closed marker with the ease of installation of an open marker. The clip mechanism allows quick and convenient installation of the marker even after the conductor has been installed. SlimFix Clips are suitable for conductors and cables with an outside diameter of up to 5 mm. The large marking surface - up to 30 mm - enables long character strings. The material is halogen-free and complies with flammability rating V2.

- Halogen-free material
- Flammability rating V2
- Fast installation without tools
- Markers in proven MultiCard format
- Available in the lengths of 12 mm, 21 mm and 30 mm

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.



### General ordering data

Type	SFC 2.5/21 MC NE GE
Order No.	<a href="#">1062070000</a>
Version	SlimFix Clip, Conductor and cable markers, 4 - 6 mm, 21 x 9.3 mm, yellow
GTIN (EAN)	4032248811793
Qty.	120 pc(s).
compatible printer	<a href="#">1324380000</a> <a href="#">2438520000</a> <a href="#">2438510000</a>

**SlimFix Clip  
SFC 2.5/21 MC NE GE**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Width	9.3 mm	Width (inches)	0.366 inch
Height	21 mm	Height (inches)	0.827 inch
Depth	9.1 mm	Depth (inches)	0.358 inch
Net weight	0.925 g		

**General data**

Colour	yellow	Halogen	No
Material	Polyamide 66	Material colour according to resistance code	4
Operating temperature range	-40...100 °C	Recommended industries	Machinery
Size of labelling field	21 x 5.8 mm	Type of printing	neutral
UL 94 flammability rating	V-2	Width	9.3 mm

**Conductor and cable markers**

Conductor O.D.	4 - 6 mm	Conductor O.D., max.	6 mm
Conductor O.D., min.	4 mm	Conductor cross-section, max.	10 mm <sup>2</sup>
Conductor cross-section, min.	4 mm <sup>2</sup>	Halogen	No

**Classifications**

ETIM 6.0	EC001530	ETIM 7.0	EC001530
eClass 9.0	27-40-04-01	eClass 9.1	27-40-04-01
eClass 10.0	27-40-04-01	UNSPSC	39-12-14-00

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Brochure/Catalogue	<a href="#">CAT 8 SAI 15/16 EN</a>
Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3,S</a>
Engineering Data	<a href="#">STEP</a>
Software	<a href="#">M-Print PRO configuration file</a>

**Data sheet**

**SlimFix Clip  
SFC 2.5/21 MC NE GE**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

