

RS-SERIES
RS U-D8 0...10V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

RS U-D8 A/D converters digitize analogue voltage signals and have 8-bit accuracy.

All modules are equipped with a hold function, so that the momentary output value is maintained even during a change to the input value.

You can find additional information describing the input/output characteristics of the A/D converter on our web site at http://www.weidmueller.com/54104/Downloads/Print-Media/ManualsOperating-instructions/cw_index.aspx.

General ordering data

Delivery status	This article will no longer be available in the future.
Available until	2021-12-31
Type	RS U-D8 0...10V
Order No.	1160361001
Version	AD converter, Input : 0-10 V, Output : 8-bit pulse
GTIN (EAN)	4032248103836
Qty.	1 pc(s).

RS-SERIES
RS U-D8 0...10V

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Length	70 mm	Length (inches)	2.756 inch
Width	35 mm	Width (inches)	1.378 inch
Height	72 mm	Height (inches)	2.835 inch
Net weight	72 g		

Temperatures

Operating temperature, max.	50 °C	Operating temperature, min.	0 °C
Storage temperature, max.	80 °C	Storage temperature, min.	-40 °C
Operating temperature	0 °C...50 °C	Storage temperature	-40 °C...80 °C

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Input

Number of inputs	1	Input voltage	0...10 V
Supply voltage (input)	24 V DC	Input resistance, voltage	≥ 400 kΩ

Output

Number of outputs	8-bit (1-bit signed)	Output level	17 V = H, 0 V = L
Output current	≤ 25mA (as source)	Cut-off frequency (-3 dB)	5 kHz at full scale (sinus)
Conversion time	≤ 4 μs		

General data

Accuracy	± 1 LSB	Current consumption	35 mA (plus output current)
Galvanic isolation	Without isolation	Input/Output	Analogue / 8 bit
Rail	TS 35, TS 32	Voltage supply	24 V DC

Insulation coordination

EMC standards	EN 61000-6	Galvanic isolation	Without isolation
---------------	------------	--------------------	-------------------

Connection data

Type of connection	Screw connection	Clamping range, rated connection	4 mm ²
Clamping range, min.	0.5 mm ²	Clamping range, max.	4 mm ²

Classifications

ETIM 6.0	EC002653	ETIM 7.0	EC002653
eClass 9.0	27-21-01-20	eClass 9.1	27-21-01-90
eClass 10.0	27-21-01-20	UNSPSC	30-21-18-01

RS-SERIES RS U-D8 0...10V

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	Declaration of Conformity
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP
User Documentation	IS RS 8BIT ADC DAC

RS-SERIES RS U-D8 0...10V

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Electric symbol

