

**P-series
BZT PRV8 SW 35X7.5**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Product image**DCS marshalling**

Our innovative PRV terminal blocks for DCS marshalling featuring a PUSH IN connection and our multifunctional DCS marshalling terminals featuring a screw connection (WMF) not only save space in the panel; they also guarantee more effective signal transmission in process control systems.

General ordering data

| | |
|------------|--|
| Type | BZT PRV8 SW 35X7.5 |
| Order No. | 1173580000 |
| Version | P-series, Marker holder, black, Number of levels: 8, TS 35 x 7.5 |
| GTIN (EAN) | 4032248966110 |
| Qty. | 20 pc(s). |

Creation date July 8, 2020 10:53:03 AM CEST

Catalogue status 08.07.2020 / We reserve the right to make technical changes.

**P-series
BZT PRV8 SW 35X7.5**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|---------|-----------------|------------|
| Width | 10.2 mm | Width (inches) | 0.402 inch |
| Height | 120 mm | Height (inches) | 4.724 inch |
| Depth | 65.6 mm | Depth (inches) | 2.583 inch |
| Net weight | 26.5 g | | |

Temperatures

| | | | |
|----------------------------------|---------------|----------------------------------|--------|
| Storage temperature, max. | 40 °C | Storage temperature, min. | 10 °C |
| Storage temperature | 10 °C...40 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 125 °C | | |

Material data

| | | | |
|---------------------------|---------------|--------|-------|
| Material | Polycarbonate | Colour | black |
| UL 94 flammability rating | V-0 | | |

System specifications

| | | | |
|---------|------------------------|------------------|---|
| Version | For the mounting rails | Number of levels | 8 |
| Rail | TS 35 x 7.5 | | |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC002848 | ETIM 7.0 | EC002848 |
| eClass 9.0 | 27-14-11-92 | eClass 9.1 | 27-14-11-92 |
| eClass 10.0 | 27-14-11-92 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|--------------------|---|
| Brochure/Catalogue | CAT 1 TERM 16/17 EN |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | STEP |
| User Documentation | StorageConditionsTerminalBlocks |