

# OMNIMATE Housing - series CH20M CH20M22 SET 1/2 BK/OR

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com











Similar to illustration

## Superior efficiency, flexibility and design - the "standard tailor-made fit"

When selecting a housing design, flexibility is a key factor. Other important criteria are: scalability, customised design, innovative functionality and cost efficiency. You need a choice which offers the maximum performance with the minimum overhead.

The CH20M22 modular electronics housing is the standard format from amongst the different housing widths. It has the optimal width for most typical electronics applications.

The entire system is characterized by excellence: outstanding scalability and flexibility, a high security level, innovative application functionality and a variety of practical details.

- Quicker installation with features such as "Wire ready" the universal multi-tool screw head
- User-friendly operations: with clear and permanent labelling and extra marking possibilities, integrated release clip or transparent cover
- Maximum interference immunity with ESDcompliant construction featuring deeply overlapping module joint edges made from high-performance plastic
- High operational reliability with the unique Auto-Set coding system and featuring double-sided touch protection on the pin header and socket blocks

CH20M - a compact name for the most flexible system available on the market. It doesn't just stand for "Component Housing IP20 Modular".

CH20M also stands for efficiency and innovation throughout design, production and use.

### General ordering data

Туре	CH20M22 SET 1/2 BK/OR
Order No.	<u>1519320000</u>
Version	Electronics housing sample, OMNIMATE Housing - series CH20M black, Sample kit for developers, consisting of individual parts incl. female plug, Width: 22.5 mm
GTIN (EAN)	4050118327120
Qty.	1 pc(s).



# OMNIMATE Housing - series CH20M CH20M22 SET 1/2 BK/OR

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

# **Technical data**

## **Dimensions and weights**

Length	119.2 mm	Length (inches)	4.693 inch
Width	22.5 mm	Width (inches)	0.886 inch
Height	113.6 mm	Height (inches)	4.472 inch
Net weight	109 g		

## **System characteristics**

Version	Sample kit for developers,	Type of connection	
	consisting of individual parts incl. female plug		pluggable
Number of connections	12	Number of connection levels	2
Number of PCBs per module	1	PCB thickness	1.6 mm
Type of contact to PCB	Solder connection, direct	Tolerance for the PCB shape	±0.1 mm
Contact to terminal rail	No	Protection degree	IP20
Encapsulation option	No		

#### **Material data**

Insulating material	PA 66 GF 30	Colour	black
Colour chart (similar)	RAL 9011	Insulating material group	II
Comparative Tracking Index (CTI)	≥ 550	UL 94 flammability rating	V-0
Max. relative humidity during storage	80 %	Operating temperature, min.	-40 °C
Operating temperature, max.	120 °C		

#### Rated data acc. to IEC

Rated current, max. number of poles		Rated current, max. number of poles	
(Tu=20°C)	10 A	(Tu=40°C)	9 A
Rated voltage for surge voltage class /		Rated voltage for surge voltage class /	
pollution degree II/2	400 V	pollution degree III/2	320 V
Rated voltage for surge voltage class /		Rated impulse voltage for surge voltage	
pollution degree III/3	250 V	class/ pollution degree II/2	250 kV
Rated impulse voltage for surge voltage		Rated impulse voltage for surge voltage	
class/ pollution degree III/2	4 kV	class/ contamination degree III/3	4 kV

#### Classifications

ETIM 6.0	EC001031	ETIM 7.0	EC001031
eClass 9.0	27-18-27-02	eClass 9.1	27-18-27-92
eClass 10.0	27-18-27-02		

# **Approvals**

ROHS	Conform		



# OMNIMATE Housing - series CH20M CH20M22 SET 1/2 BK/OR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

# **Drawings**

