

**VPK EX (Ex blanking plug in plastic)  
VP M32-EXE SW**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



For sealing surplus threaded holes to maintain the IP class of protection

**General ordering data**

|            |                                                                                         |
|------------|-----------------------------------------------------------------------------------------|
| Type       | VP M32-EXE SW                                                                           |
| Order No.  | <a href="#">1737100000</a>                                                              |
| Version    | VPK EX (Ex blanking plug in plastic), Blanking plug, M 32, 15 mm, IP66, IP68, Polyamide |
| GTIN (EAN) | 4008190956578                                                                           |
| Qty.       | 100 pc(s).                                                                              |

**VPK EX (Ex blanking plug in plastic)**  
**VP M32-EXE SW**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Length     | 20.5 mm | Length (inches) | 0.807 inch |
| Net weight | 10.4 g  |                 |            |

**Certificate numbers cable gland**

|                                    |                    |                                     |                    |
|------------------------------------|--------------------|-------------------------------------|--------------------|
| Certificate no. cable gland (ATEX) | LCIE 08 ATEX 6085X | Certificate no. cable gland (IECEx) | IECEx LCI 08.0035X |
| Identification                     | Ex e II, Ex tD     |                                     |                    |

**General information**

|                                   |                                                                                                                                                                                                                                                                                              |                                   |            |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|------------|
| Material                          | Polyamide                                                                                                                                                                                                                                                                                    | Cable glands                      | metric     |
| External thread                   | M 32                                                                                                                                                                                                                                                                                         | Pitch of thread                   | 1.5 mm     |
| Length of thread                  | 15 mm                                                                                                                                                                                                                                                                                        | AF size 1                         | 36 mm      |
| Protection degree                 | IP54, IP66                                                                                                                                                                                                                                                                                   | Protection degree with GWDR       | IP66, IP68 |
| Operating temperature range, min. | -20 °C                                                                                                                                                                                                                                                                                       | Operating temperature range, max. | 80 °C      |
| UL 94 flammability rating         | V-2                                                                                                                                                                                                                                                                                          | Halogen                           | No         |
| Note: protection class            | IP54 in accordance with EN 60529 standard, minimal without flat gasket; IP66 in accordance with EN 60529, minimal without flat gasket; IP68 in accordance with EN 60529 with flat gasket; Except for 2D application, as specified in the Ex-Certificate, a flat gasket is required for IP66. |                                   |            |

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000451    | ETIM 7.0   | EC000451    |
| eClass 9.0  | 27-14-44-25 | eClass 9.1 | 27-14-44-35 |
| eClass 10.0 | 27-14-44-25 | UNSPSC     | 30-21-18-01 |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                                                                           |
|--------------------|---------------------------------------------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 3 HDC 17/18 EN</a><br><a href="#">CAT 5 ENCL 17/18 EN</a> |
| Engineering Data   | <a href="#">EPLAN, WSCAD</a>                                              |
| Engineering Data   | <a href="#">STEP</a>                                                      |

### VPK EX (Ex blanking plug in plastic) VP M32-EXE SW

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

