

**VPK (blanking plug in plastic)
VP M40 K54****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



For sealing surplus threaded holes to maintain the IP
class of protection

General ordering data

Type	VP M40 K54
Order No.	1776950000
Version	VPK (blanking plug in plastic), Blanking plug, M 40, 13 mm, IP65, Polyamid 6 (PA6 - GF30)
GTIN (EAN)	4032248156399
Qty.	25 pc(s).

VPK (blanking plug in plastic) VP M40 K54

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	7 mm	Length (inches)	0.276 inch
Net weight	10.16 g		

General information

Material	Polyamid 6 (PA6 - GF30)	Cable glands	metric
External thread	M 40	Pitch of thread	1.5 mm
Length of thread	13 mm	Protection degree	IP54
Protection degree with GWDR	IP65	Operating temperature range, min.	-40 °C
Operating temperature range, max.	100 °C	Head diameter	46 mm
UL 94 flammability rating	V-2	Halogen	No

Classifications

ETIM 6.0	EC000451	ETIM 7.0	EC000451
eClass 9.0	27-14-44-25	eClass 9.1	27-14-44-33
eClass 10.0	27-14-44-25	UNSPSC	30-21-18-01

Approvals

Approvals



ROHS Conform

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP

VPK (blanking plug in plastic) VP M40 K54

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

