

**Industrial Ethernet
IE-PM-RJ45-TH****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



RJ45 crimp plug-in connector according to IEC
60603-7-51 for wire outer diameters up to 1.05 mm

General ordering data

Type	IE-PM-RJ45-TH
Order No.	1963580000
Version	RJ45 crimp plug, Plug without bending protection sleeve, Cat.6 _A / Class E _A (ISO/IEC 11801 2010)
GTIN (EAN)	4032248645688
Qty.	100 pc(s).

Industrial Ethernet IE-PM-RJ45-TH

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Net weight	3.46 g
------------	--------

Temperatures

Operating temperature, max.	70 °C	Operating temperature, min.	-40 °C
Operating temperature	-40 °C...70 °C		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General data

Connection 1	RJ45	Connection 2	IDC
Description of article		Configuration	Connects piercing contacts and shielded connections in one step, retro-fit for kink-prevention sleeves, Multi-port compatible
	Plug without bending protection sleeve		
Colour	Miscellaneous	Housing main material	Brass, PC UL 94 V0
Insulation cross-section, min.	0.85 mm	Insulation cross-section, max.	1.05 mm
Cable pull-out force, min.		Category	Cat.6A / Class E _A (ISO/IEC 11801 2010)
	89 N	Contact surface	Gold-plated
Contact material	Phosphorus bronze	Conductor connection cross-section, solid (AWG)	AWG 27...AWG 24
Connection diameter, solid	0.36...0.51 mm	Conductor connection cross-section, flexible (AWG)	AWG 27...AWG 24
Connection diameter, flexible	0.46...0.61 mm	MICE classification I	I ₁
MICE classification M	M ₁	MICE classification E	E ₃
MICE classification C	C ₁	Sheath diameter, max.	7.3 mm
Sheath diameter, min.	5 mm	Shielding material	0.5 mm brass, 2 µm nickel
Bending protection sleeve material	Polycarbonate PC, UL 94 V-0	Protection degree	IP20
Shielding	360° all-round enclosure	Material insulator	Polycarbonate PC, UL 94 V-0
Plugging cycles	750		

Electrical properties

Contact resistance	≤ 20 mΩ	Current-carrying capacity at 50 °C	1 A
Dielectric strength, contact / contact	≤ 1000 V DC	Dielectric strength, contact / shield	≤ 1500 V DC
Insulation strength	500 MΩ	PoE / PoE+	conforming to IEEE 802.3af

General standards

Certificate No. (cURus)	E316369	Connector standard	IEC 60603-7-51
-------------------------	---------	--------------------	----------------

Classifications

ETIM 6.0	EC001121	ETIM 7.0	EC001121
eClass 9.0	27-44-03-90	eClass 9.1	27-44-03-90
eClass 10.0	27-44-03-90	UNSPSC	30-21-18-10

**Industrial Ethernet
IE-PM-RJ45-TH****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data**Approvals**

Approvals



ROHS

Conform

DownloadsApproval/Certificate/Document of
Conformity

[GOST Approval](#)
[ISO/IEC EN and TIA/EIA Screened Class EA Category 6A, 4 connector channel](#)
[C-Link IE-PS-RJ45-TH-BK](#)
[UL Approval](#)

Brochure/Catalogue

[CAT 9 IETH 18/19 EN](#)
[MB FREECONTACT EN](#)
[FL FIELDWIRING EN](#)
[PI PROFINET CABLING EN](#)

Engineering Data

[WSCAD](#)

User Documentation

[MAN IE GUIDE DE](#)
[MAN IE GUIDE EN](#)
[Manual](#)

Industrial Ethernet IE-PM-RJ45-TH

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Dimensioned drawing

