

Dekafix DEK 5/5 MM WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

General ordering data

| | |
|--------------------|--|
| Type | DEK 5/5 MM WS |
| Order No. | 2007110000 |
| Version | Dekafix, Terminal marker, 5 x 5 mm, Weidmueller, white |
| GTIN (EAN) | 4050118391862 |
| Qty. | 800 pc(s). |
| compatible printer | 2599430000 2599440000 |

Data sheet

Dekafix DEK 5/5 MM WS

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Width | 5 mm | Width (inches) | 0.197 inch |
| Height | 5 mm | Height (inches) | 0.197 inch |
| Net weight | 0.077 g | | |

General data

| | | | |
|-----------------------------|-------------|-------------------------|---------------------------------|
| Application/manufacture | Weidmueller | Colour | white |
| Halogen | No | Material | PC-ABS, TPU |
| Operating temperature range | -50...90 °C | Size of labelling field | 4.5 x 4.7 mm |
| UL 94 flammability rating | V-2 | Version | with clip-in foot, halogen-free |
| Width | 5 mm | | |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000761 | ETIM 7.0 | EC000761 |
| eClass 9.0 | 27-14-11-37 | eClass 9.1 | 27-14-11-37 |
| eClass 10.0 | 27-14-11-37 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|-----------------------------|--|
| Brochure/Catalogue | CAT 1 TERM 16/17 EN |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | STEP |
| Product Change Notification | MultiMark_PCN_de_Extern MultiMark_PCN_en_external |

Data sheet

**Dekafix
DEK 5/5 MM WS**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Example of use

