


## Connecting elements H95,0/44 R

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



- supplied loose in poly-bag
- Weidmüller colour code
- DIN colour code

### General ordering data

|            |                                                |
|------------|------------------------------------------------|
| Type       | H95,0/44 R                                     |
| Order No.  | <a href="#">9028210000</a>                     |
| Version    | Wire-end ferrule, insulated, 31 mm, 25 mm, red |
| GTIN (EAN) | 4008190891589                                  |
| Qty.       | 25 pc(s).                                      |
| Packaging  | loose                                          |

## Connecting elements

### H95,0/44 R

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Dimensions and weights

|            |       |
|------------|-------|
| Net weight | 5.2 g |
|------------|-------|

### Technical data

|         |           |
|---------|-----------|
| Version | insulated |
|---------|-----------|

### Wire-end ferrules

|                             |                    |                                         |            |
|-----------------------------|--------------------|-----------------------------------------|------------|
| Collar diameter (D2)        | 18 mm              | Colour code                             | Weidmüller |
| Conductor cross-section     | 95 mm <sup>2</sup> | Contact surface diameter (D1)           | 14.7 mm    |
| Contact surface length (L2) | 25 mm              | L1 in mm                                | 44 mm      |
| Metal sleeve thickness (S1) | 0.35 mm            | Plastic collar thickness (S2)           | 0.6 mm     |
| Stripping length            | 31 mm              | Wire connection cross section AWG, max. | AWG 3/0    |

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0   | EC000005    |
| eClass 9.0  | 27-40-02-01 | eClass 9.1 | 27-40-02-01 |
| eClass 10.0 | 27-40-02-01 | UNSPSC     | 31-16-31-02 |

### Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 6 TOOLS 15/16 EN</a>                                                     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| Engineering Data   | <a href="#">STEP</a>                                                                     |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |

### Connecting elements H95,0/44 R

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Drawing

